



Remet
Datasheet
600

REMET
PARAFFIN WAX

REMET Paraffin waxes are fully refined mineral waxes for use in a wide range of applications

REMET offers a range of paraffin waxes at different melting points to suit your application.

These waxes meet the FDA requirement 21 CFR 172.886

Applications

- Candles
- Paper Converting
- Adhesives
- Anti Ozone Blends for Tyre and Rubber
- Wax Blends and Emulsions
- Paper Cup and Packaging Coating/Impregnating

Typical Properties

	FR 54/56	FR 56/58	FR 58/60	FR 64/66
Melting Point °C (°F)	54 - 56 (129-133)	56 - 58 (133-136)	58 - 60 (136-140)	64 - 66 (147-151)
Oil Content	< 0.5%	< 0.5%	< 0.5%	< 0.5%
Colour, Saybolt	> 28	> 25	> 27	> 27
Penetration @ 25°C	< 18	< 18	< 18	< 18
Odor	< 1	< 1	< 1	< 1

Tariff Code

27122000 - Paraffin Wax Containing by Weight Less than 0.75% of Oil.

Packaging

25kg Cartons, 40 cartons per pallet

Health and Safety

Read SDS prior to use

Storage and Handling

Store in a cool dry location

Disposal

Dispose of in compliance with all local and national regulations

Information and/or recommendations based on research and technical data believed to be reliable. Offered free of charge for use by persons with technical skills, at their own discretion and risk, without guarantee of accuracy REMET makes no warranties, express or implied, and assumes no liability as to the use of its products or of any information pertaining thereto. Nothing herein is intended as a recommendation to infringe any patent.

REMETS UK LTD
44 Riverside II, Sir Thomas Longley Road
Rochester, Kent ME2 4DP, UK

T: +44 (0) 1634 226 240
F: +44 (0) 1634 226 241
E: Enquiries@remetuk.com

YOUR CONCEPT TO CASTING PARTNER