

SILICONES

and more

A1 Sealer Plus

A1 Sealer PLUS is a water-based coating to protect A1 acrylic resin against weather influences such as UV and moisture. A1 Sealer PLUS is a concentrated solution of high-quality acrylates in water. The A1 Sealer PLUS is a so-called breathable coating. **Specificaties**

- Minimum processing temperature: 10°C
- Average consumption: 8-10 m² per liter

Processing

The object to be treated must be completely dry. For acrylic resin or plaster objects, we recommend waiting at least 48 hours before applying the sealer.

The surface to be sealed must be free of wax, oil, dirt or dust. Apply with a brush, roller, wipe with a soft cloth or spray.

If the A1 Sealer PLUS is applied with a brush, we recommend adding 30% water. After applying the A1 Sealer PLUS with a brush, the A1 Sealer PLUS should be rubbed with a dry cloth while it is still damp. In this way, apply a maximum of 3 layers of A1 Sealer PLUS to the A1 object. These layers can be applied one after the other with a short drying time of a few minutes. The consumption of A1 Sealer PLUS per kg brush is 8 to 10 m².

When spraying the A1 Sealer PLUS, we recommend adding up to 50% water. Polishing is not necessary due to the atomization of the A1 Sealer PLUS. The consumption when spraying the A1 Sealer per kg is 10 to 12 m².

Avoid applying too thick a layer of A1 Sealer PLUS as this will seal the A1 object. We recommend to inspect the treated surface every year and, if necessary, to treat it again every 6 years with A1 Sealer PLUS. This creates an expected life of the A1 property of 50 years.

You have the choice between A1 Sealer PLUS Matt, A1 Sealer PLUS Satin and A1 Sealer PLUS Satin. For the mattest result, we recommend first applying a layer of A1 Sealer PLUS Satin and then a layer of A1 Sealer PLUS Matt.

Shelf life

1 year in closed packaging if stored cool, dry, frost-free and out of direct sunlight

Safety requirements

Always wear protective gloves when handling this product. Always work in a well-ventilated area. For further information, see safety data sheets.

Characteristics

- 1 component
- Solvent free
- Water-based
- Quick drying
- Easy to apply
- Good UV resistance
- Excellent adhesion
- Protection against dirt absorption
- Good protection against moisture

