



Remet Datasheet

WAX ROOM - CASTING WAX Wax Allround

Wax Allround is a reclaim based casting wax, that offers stable wax parts at an economical price.

The Wax Allround is a 100% reclaimed wax that has been filtered to remove any impurities or foreign objects from the wax. It is available in two types:

Wax Allround is made from reclaimed wax that has been filtered by centrifuge.

The wax offers a very economical casting wax solution for foundries on a tight budget.

Typical Properties

		Wax Allroundt
Melt Point (°C)		68 - 74
Congeaing Point (°C)		62 - 68
Penetration @ 25°C (dmm)		3 - 8
Viscosity (cSt)		200 - 900 (@ 80°C)
Ash Content (%)		0.20 (Max)
Colour	Brown / Green	

Tariff Code

34049000 - Artificial & Prepared Waxes

Packaging

Available in 25kg Bags

Health and Safety

Read SDS prior to use.

Storage and Handling

Store in a cool dry location.
Keep away from direct sunlight

Disposal

Dispose of in compliance with all local and national regulations.

Information and/or recommendations based on research and technical data believed to be reliable. Offered free of charge for use by persons with technical skills, at their own discretion and risk, without guarantee of accuracy REMET makes no warranties, express or implied, and assumes no liability as to the use of its products or of any information pertaining thereto. Nothing herein is intended as a recommendation to infringe any patent.

REMET UK LTD
44 Riverside II, Sir Thomas Longley Road
Rochester, Kent ME2 4DP, UK

T: +44 (0) 1634 226 240
F: +44 (0) 1634 226 241
E: CustomerService@remetuk.com

YOUR CONCEPT TO CASTING PARTNER