SILICONES and more

Acrylic Resin Sealer Matt

Increase your acrylic product life expectancy to 30 years.

Description

Acrylic sealer dull is a water-based coating to protect your acryl model from moisture and make it weatherproof.

Processing

Acrylic sealer dull is a concentrated solution of acrylic polymers in water. Before use shake the bottle well.

Best to apply in 2 layers. First layer diluted with 10% water. Second layer undiluted. For proper sealing the surface must be free of wax, oil, dirt or dust. Apply using brush, roller, wiping with a soft cloth or by spraying.

Acrylic Sealer dull can be applied in one or several layers in order to improve the protective properties. Depending on temperature and humidity it can be reapplied after 45 minutes. When only one layer is applied with a soft cloth this will result in a dull effect. If several layers are applied you will obtain a more shiny effect.

Special instructions

Please only process at temperature between 10 and 30 ° C

The advantages are: one component, solvent-free, water-based, quick drying, easy to apply, good UV resistance, excellent adhesion, protection against absorption of dirt and protection against moisture.

Coverage 12-16 m² / Kg

Drying time: 15 minutes to 1 hour depending on

Packing

The Acrylic Sealer Matt is available in a 250 ml bottle enough for 2 to 2.5 m^2 on average use.

Durability

Provided the components are stored in sealed containers in a cool and frost-free place out of direct sunlight, the shelf life is at least 1 year.

Safety

When in contact with skin or eyes rinse with plenty of water. When ingested do not induce vomiting. Consult doctor when symptoms persist.



Characteristics

Matt finish

• More shiny after multiple layers