

Material: 60033140 ELASTOSIL® M 4644 B

Version: 1.3 (INTL-GHS) Date of print: 03.03.2021 Date of last alteration: 20.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial product name: ELASTOSIL® M 4644 B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:

Industrial.

Raw material for: elastomer products.

1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor: Wacker Chemie AG
Street/POB-No.: Hanns-Seidel-Platz 4
State/postal code/city: D 81737 München
Telephone: +49 89 6279-0
Telefax: +49 89 6279-1770

Information about the Safety Data Sheet: Telephone +49 8677 83-4888

Telefax +49 8677 886-9722

eMail WLCP-MSDS@wacker.com

1.4 Emergency telephone number

Emergency Information: Europe +44 1235 239670
Emergency Information: Africa and the Middle East +44 1235 239671
Emergency Information: Caribbean, Central America and South +1 646 844 7309

America except Chile and Colombia

Emergency Information:

Chile
+56 2 2582 9336

Emergency Information:

Colombia
+57 1 508 7337

Emergency Information:

East Asia and Southeast Asia except
+65 3158 1074

Sri Lanka, Bangladesh and Pakistan

Emergency Information:

Emergency Information:

Emergency Information:

Emergency Information:

Emergency Information:

Emergency Information:

Pakistan

+65 3158 1195

+65 3158 1290

+65 3158 1329

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

2.2 Label elements

No labeling according to GHS required.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

Polydimethylsiloxane with functional groups

3.2.2 Hazardous ingredients

This material does not contain any ingredients above the permitted limit(s).

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above ≥ 0.1%.

Page: 1/8



Material: 60033140 ELASTOSIL® M 4644 B

Version: 1.3 (INTL-GHS) Date of print: 03.03.2021 Date of last alteration: 20.11.2019

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).

After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

After contact with the skin:

Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

After inhalation:

Provide fresh air.

After swallowing:

Give several small portions of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Fires can be controlled with water spray, foam or carbon dioxide. Larger fires are best fought with alcohol-resistant aqueous film forming foam (AFFF-AR).

Extinguishing media which must not be used for safety reasons:

water jet, extinguishing powder, halones.

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: toxic and very toxic fumes. With the use of water-based extinguishing agents care is required because hydrogen can be released, which accumulates after extinguishing the fire in poorly ventilated or confined areas and may refire or cause an explosion. Foam carpets may also include hydrogen or flammable vapors, which can lead to surface bursts. Remove sources of ignition during cleaning and absorbing.

5.3 Advice for firefighters

Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air. Keep unprotected persons away.

General information:

Fires involving SiH polysiloxane materials can be difficult to extinguish under certain circumstances.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Page: 2/8



Material: 60033140 ELASTOSIL® M 4644 B

Version: 1.3 (INTL-GHS)

Date of print: 03.03.2021

Date of last alteration: 20.11.2019

6.3 Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. Use only air driven or properly rated electrical eqiupment. Use vented recovery containers. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Do not blend contaminated material with uncontaminated material. Do not seal collecting vessel gas-tight. Observe notes under section 7.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Precautions for safe handling:

Ensure adequate ventilation. Open and handle container with care. Keep container closed when not in use. Keep away from incompatible substances in accordance with section 10. Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

Precautions against fire and explosion:

Product can release hydrogen. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Conditions for safe storage, including any incompatibilities

Conditions for storage rooms and vessels:

Do not store in virgin glass containers with basic surface. Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Maximum airborne concentrations at the workplace:

CAS No. Substance	Type	mg/m³	ppm	Dust fract.	Fibre/m ³
Aerosol - inhalable fraction		10,0			

The aerosol limit specified is a recommendation should aerosol be formed during processing.

8.2 Exposure controls

8.2.1 Exposure in the work place limited and controlled

General protection and hygiene measures:

Observe standard industrial hygiene practices for the handling of chemical substances. Do not eat, drink or smoke when handling.

Personal protection equipment:

Respiratory protection

No personal respiratory protective equipment normally required.

Page: 3/8



Material: 60033140 ELASTOSIL® M 4644 B

Version: 1.3 (INTL-GHS)

Date of print: 03.03.2021

Date of last alteration: 20.11.2019

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Filtering half-face mask, according to acknowledged standards such as EN 149.

Recommended Filter type: FFP1 or equivalent filter, according to acknowledged standards such as EN 149

Observe the equipment manufacturer's information and wear time limits for respirators.

Eye protection

Recommendation: protective goggles .

Hand protection

Use of protective gloves is recommended when handling the material.

Recommended glove types: Protective gloves made of nitrile rubber

thickness of the material: > 0,1 mm Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of butyl rubber

thickness of the material: > 0,3 mm Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

8.3 Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

SECTION 9: Physical and chemical properties

9.1	Information on basic physical and chemical properties			
	Property:	Value:	Method:	
	Appearance			
	Physical state:	liquid		
-	Colour	colourless		
	Odour			
	Odour:	odourless		
	Odour limit			
	Odour limit:	no data available		
	pH-Value			
	pH-Value:	not applicable		
	Melting point/freezing point			
	Melting point / melting range	not applicable		
	Initial boiling point and boiling range			
	Boiling point / boiling range	not applicable		
	Flash point			
	Flash point:	ca. 311 °C	(DIN 51376)	
	Evaporation rate			
	Evaporation rate:	no data available		
	Upper/lower flammability or explosive limits			
	Lower explosion limit (LEL)	• •		
	Upper explosion limit (UEL)	not applicable		
	Vapour pressure			
	Vapour pressure	not applicable		
	Solubility(ies)			
	Water solubility / miscibility:	virtually insoluble		
	Vapour density			
	Relative gas/vapour density	No data known.		



Material: 60033140 ELASTOSIL® M 4644 B

Version: 1.3 (INTL-GHS)

Date of print: 03.03.2021

Date of last alteration: 20.11.2019

Relative Density

Relative Density ca. 0,97 (25 °C; 1013 hPa)

(Water / $4 \, ^{\circ}\text{C} = 1,00$)

(DIN 51757)

Partition coefficient: n-octanol/water

Partition coefficient: n-octanol/water...... No data known.

Auto-ignition temperature

Decomposition temperature

Thermal decomposition > 200 °C

Viscosity

Molecular mass

Molecular mass not applicable

9.2 Other information

Explosion limits for released hydrogen: 4 - 75.6%(V).

SECTION 10: Stability and reactivity

10.1 - 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

none known

10.5 Incompatible materials

Reacts slowly with: basic substances (e.g. alkalis, ammonia, amines), strong acids, oxidizing agents. Reaction causes the formation of: hydrogen.

10.6 Hazardous decomposition products

Upon contact with the substances mentioned in 10. hydrogen . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Product details:

Route of exp	osure Result/Effect	Species/Test system	Source
Oral	LD50: > 2000 mg/kg	Rat	Conclusion by analogy
dermal	LD50: > 2000 mg/kg	Rat	Conclusion by analogy

11.1.2 Skin corrosion/irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	Rabbit	Conclusion by
		analogy

11.1.3 Serious eye damage / eye irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	Rabbit	Conclusion by
		analogy

Page: 5/8



Material: 60033140 ELASTOSIL® M 4644 B

Version: 1.3 (INTL-GHS)

Date of print: 03.03.2021

Date of last alteration: 20.11.2019

11.1.4 Respiratory or skin sensitization

Product details:

Route of expos	sure Result/Effect	Species/Test system	Source
dermal	not sensitizing	Guinea pig; Buehler Test	Conclusion by
			analogy
			OECD 406

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

SECTION 12: Ecological information

12.1 Toxicity

Assessment:

Assessment based on ecotoxicological tests with similar products under consideration of the physical-chemical properties: For this product no effects on aquatic organisms, relevant for classification, are expected. According to current knowledge adverse effects on water purification plants are not expected.

12.2 Persistence and degradability

Assessment:

Silicone content: biologically not degradable. Separation by sedimentation.

12.3 Bioaccumulative potential

Assessment:

Polymer component: No adverse effects expected.

12.4 Mobility in soil

Assessment:

Silicone content: Insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

Page: 6/8



Material: 60033140 ELASTOSIL® M 4644 B

Version: 1.3 (INTL-GHS)

Date of print: 03.03.2021

Date of last alteration: 20.11.2019

12.6 Other adverse effects

none known

12.7 Additional information

Easily separable from water by filtration.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Material

Recommendation:

Risk of oxyhydrogen formation upon contact with the substances mentioned in 10. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Wastes of this material should not be mixed with other wastes. Provide measures such as vented bungs to ensure pressure relief in the waste containers. Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging

Recommendation:

Containers may contain hazardous quantities of hydrogen gas. Uncleaned containers should not be reused to hold another material due to the potential for reaction between residual product and incompatible materials. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

SECTION 14: Transport information

14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

Road ADR:

Valuation Not regulated for transport

Railway RID:

Valuation Not regulated for transport

Transport by sea IMDG-Code:

Valuation Not regulated for transport

Air transport ICAO-TI/IATA-DGR:

Valuation Not regulated for transport

14.5 Environmental hazards

Hazardous to the environment: no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

15.2 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan : ENCS (Handbook of Existing and New Chemical Substances):

This product is listed in, or complies with, the substance inventory.



Material: 60033140 ELASTOSIL® M 4644 B

Version: 1.3 (INTL-GHS)

Date of print: 03.03.2021

Date of last alteration: 20.11.2019

Australia : AICS (Australian Inventory of Chemical Substances):

This product is listed in, or complies with, the substance inventory.

China...... IECSC (Inventory of Existing Chemical Substances in China):

This product is listed in, or complies with, the substance inventory.

Canada : DSL (Domestic Substance List):

This product is listed in, or complies with, the substance inventory.

United States of America (USA)...... TSCA (Toxic Substance Control Act Chemical Substance Inventory):

All components of this product are listed as active or are in compliance with the

substance inventory.

This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of

this obligation.

European Economic Area (EEA)...... : REACH (Regulation (EC) No 1907/2006):

General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA

General note: in case of registration obligations for substances or polymers imported into Korea or manufactured within Korea these are fulfilled by the supplier mentioned in section 1. The registration obligations for substances or polymers imported into Korea by customers or other downstream users must be fulfilled by

the latter.

SECTION 16: Other information

16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

- End of Safety Data Sheet -

Page: 8/8