

# Safety Data Sheet

In accordance with directive 1907/2006/EC, 2015/830

Page: Page 1of 9

Version 1.0

Date of issue: 28-08-2020

Print date: 29-6-2021

Trade name: Polyurethane

Casting Resin Flexible A60 B

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking** 1.1 Product identification:

Product name: Polyurethane Casting Resin Flexible A60 B

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Usage: Polyurethane rubber component.

### 1.3 Details of the supplier of the safety data sheet

Responsible distributor :  
Nedform BV  
Hofdwardsweg 20  
6161DD Geleen  
The Netherlands  
Tel: +31 464106260  
Website: [www.nedform.com](http://www.nedform.com)

### 1.4 Emergency Telephone Number

For Belgium:

Email: [info@nedform.com](mailto:info@nedform.com)

NHS 24 Direct

Call the **Poison Control Center (070 245 245 - free)**, if not available: **02 264 96 30** (normal rate) or your doctor. In life-threatening situations, always call the European emergency number **112**.  
For help from a GP, visit your GP surgery's website, use an online service to contact your GP, or call the surgery.  
**For urgent medical help**, use the NHS 111 online service, or **call 111** if you are unable to get help online.  
**For life-threatening emergencies, call 999** for an ambulance. There is more information about getting medical help on the NHS website.

## **SECTION 2: Hazard identification**

### 2.1 Classification of the substance or mixture:

**Classification according to Directive (EC) No 1272/2008 and its amendments.**

The product is classified according to the applicable legislation.

**Classification in accordance with Regulation (EC) No 1272/2008 as amended.**

#### **Health hazards**

Warning, Eye Irrit. 2, Causes serious eye irritation.

Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

#### **Adverse physicochemical effects, effects on human health and the environment:**

No other hazards

### 2.2 Label elements:

**Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]:**



**Hazard pictograms:**

**Signal word**

Warning.

**Indications of danger:**

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

**Precautions**

**Prevention:**

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P314 If you feel unwell, seek medical advice.

# Safety Data Sheet

In accordance with directive 1907/2006/EC, 2015/830

Page: Page 2 of 9

Version 1.0

Date of issue: 28-08-2020

Print date: 29-6-2021

Trade name: Polyurethane Casting

Resin Flexible A60 B

P337 + P313 If eye irritation persists: Call a doctor.

P391 Collect spillages.

P501 Dispose of contents/container in accordance with applicable regulations.

## Special provisions:

No

## Contains:

✓ Diethylmetilbenzidiamina

## Special provisions according to Annex XVII of REACH and subsequent amendments:

No

## 2.3 Other hazards:

vPvB-substances: None - PBT Substances None

## Other hazards:

No other hazards

## SECTION 3: Composition and information on ingredients

### 3.2 Mixtures:

#### Description:

Hazardous components within the meaning of the CLP regulation and related classification:

Chemical Name	Cas No. EC No/List Registration number	Layout (Regulation (EC) No 1272/008)	Concentration (%)
Dipropylene glycol, dibenzoate	27138-31-4 248-258-5 01-2119529241-49	Aquatic Chronic 3 H412	>= 80%
Diethylmetilbenzidiamina	68479-98-1 270-877-4	Acute Tox. 4 H312 Acute Tox. 4 H302 Eye Irrit. 2 H319 STOT RE 2 H373 Aquatic Acute 1 H400 Aquatic Chronic 1 H410	>= 10% - < 20%

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures:

#### In case of skin contact:

Remove contaminated clothing immediately.

Areas of the body that have been in contact, or are suspected of having been in contact, with the product should be immediately rinsed with plenty of running water and, if necessary, with soap.

Wash the body thoroughly (shower or bath).

Remove contaminated clothing immediately and dispose of it safely.

After contact with skin, wash immediately with soap and plenty of water.

#### In case of eye contact:

After contact with eyes, rinse with water for a sufficient period of time with the eyelids open, then consult an ophthalmologist immediately.

Protect uninjured eye.

#### In case of ingestion:

Under no circumstances induce vomiting. GET A MEDICAL EXAMINATION IMMEDIATELY.

#### In case of inhalation:

Take the victim into the fresh air and keep him warm and calm.

### 4.2 Most important symptoms and effects, both acute and delayed:

#### Appearances:

No

### 4.3 Indication of any immediate medical attention and special treatment needed:

# Safety Data Sheet

In accordance with directive 1907/2006/EC, 2015/830

Page: Page 3 of 9

Version 1.0

Date of issue: 28-08-2020

Print date: 29-6-2021

Trade name: Polyurethane

Casting Resin Flexible A60 B

In case of accident or feeling unwell, seek medical advice immediately (show the instructions for use or the Safety Data Sheet where possible).

**Treatment:**

No

**SECTION 5: Fire-fighting measures**

**5.1 Extinguishing media:**

**Suitable extinguishing media:**

Water.

Carbon dioxide (CO<sub>2</sub>).

**Extinguishing media which must not be used for safety reasons:**

None in particular.

**5.2 Special hazards arising from the substance or mixture**

**Specific fire fighting hazards:**

Do not inhale explosion gases or combustion gases.

Burning produces heavy smoke.

**5.3 Advice for firefighters:**

**Special protective equipment for firefighters:**

Use suitable respiratory equipment.

Collect contaminated extinguishing water separately. It may not be discharged into the sewage system.

Move undamaged containers out of the immediate danger zone if this can be done safely.

**SECTION 6: Accidental release measures for the substance or mixture**

**6.1 Personal precautions, protective equipment and emergency procedures:**

**Personal precautions:**

Wear personal protective equipment.

Bringing people to safety.

See protective measures under points 7 and 8.

**6.2 Environmental precautions:**

**Environmental precautions:**

Do not allow to enter soil/subsoil. Do not allow to enter surface water or the sewage system.

Collect and dispose of contaminated wash water.

In the event of gas escape or entry into waterways, soil or sewage system, inform the responsible authorities.

Suitable material for absorption: absorbent material, organic, sand.

**6.3 Methods and material for containment and cleaning up**

**Cleaning methods:**

Wash with plenty of water.

**6.4 Reference to other sections:**

See also section 8 and 13.

**SECTION 7: Handling and storage:**

**7.1 Precautions for safe handling**

Avoid contact with skin and eyes, inhalation of vapours and spray.

Do not use empty containers before they have been cleaned.

Make sure that there are no incompatible materials in the containers before carrying out transfer operations.

Soiled clothing should be changed before entering eating areas.

Do not eat or drink during work.

See also section 8 for recommended protective equipment.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in original containers, dry, tightly closed, in a cool and well-ventilated area.

Avoid contact with skin, eyes and clothing.

Keep away from food, drink and feed.

# Safety Data Sheet

In accordance with directive 1907/2006/EC, 2015/830

Page: Page 4 of 9

Version 1.0

Date of issue: 28-08-2020

Print date: 29-6-2021

Trade name: Polyurethane

Casting Resin Flexible A60 B

Mismatched materials: None in particular.

Instructions on storage areas: Sufficiently ventilated rooms.

7.3 Specific end use:

None in particular.

## **SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters:**

No occupational exposure limit available

### **DNEL exposure limits**

Dipropylene glycol, dibenzoate - CAS: 27138-31-4

Worker Industry: 8.8 mg / m<sup>3</sup> - Consumer: 8.69 mg / m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long-term, systemic effects

Worker Industry: 35.08 mg / m<sup>3</sup> - Consumer: 8.7 mg / m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short term, systemic effects

Worker Industry: 10 mg / kg - Consumer: 0.22 mg / kg - Exposure: Human Skin - Frequency: Long term, systemic effects - Comments: bw / day

Consumer: 80 mg / kg - Exposure: Human Dermal -

Frequency: short term, systemic effects - Comments: bw / day

Workers: 5 mg / kg - Exposure: Human Oral - Frequency: Long-term, systemic effects

Dietilmetilbenzendiammina - CAS: 68479-98-1

Consumer: 0.100 mg / kg - Exposure: Human Oral - Frequency: Long-term, systemic effects

Worker Industry: 1,000 mg / kg - Consumer: 1,000 mg / kg - Exposure: Human Dermal - Frequency: long-term, systemic effects

Worker Industry: 0.130 mg / m<sup>3</sup> - Consumer: 0.100 mg / m<sup>3</sup> - Exposure: Human Inhalation - Frequency: long-term, systemic effects

### **PNEC exposure limits**

Dipropylene glycol, dibenzoate - CAS: 27138-31-4

Purpose: Sea water - Value: 3.7 03

Objective: 08 - Value: 1 mg / kg - Comments: Soil dw

Dietilmetilbenzendiammina - CAS: 68479-98-1

Objective: Freshwater sediment - Value: 29,000 mg / kg

Objective: Marine sediment - Value: 2,900 mg / kg

Objective: Freshwater - Value: 0.500 mg/m<sup>3</sup>

Target: Marine water - Value: 0.050 mg / m<sup>3</sup>

**8.2 Exposure controls:**

#### **Eye protection:**

Wear safety goggles (ref. Standard EN 166).

#### **Protection for the skin:**

Safety shoes.

Wear long-sleeved working clothes and safety shoes for professional use of category I (REF. Dir. 89/686 / EEC and EN 344).

#### **Protection for hands:**

Protect your hands with work gloves (ref. Directive 89/686 / EEG and its amendments and EN 374/2003)

#### **Respiratory protection:**

Use suitable protective breathing equipment. (Ref. Dir. 89/686 / EEC as amended - UNI PROTECTED / 1998 - UNI EN 529/2006)

#### **Thermal hazards:**

No

#### **Controlling environmental exposure:**

Avoid entering sewers, basements or other places where accumulation can be dangerous.

#### **Appropriate technical measures:**

No

# Safety Data Sheet

In accordance with directive 1907/2006/EC, 2015/830

Page: Page 5 of 9

Version 1.0

Date of issue: 28-08-2020

Print date: 29-6-2021

Trade name: Polyurethane

Casting Resin Flexible A60 B

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties:

Appearance:	liquid
Colour:	amber
Odour:	low
Odour threshold:	Not implemented
pH:	Not performed
Melting/freezing point	Not applicable
Boiling point/boiling range	Not applicable
Flash point	Not applicable
Evaporation rate:	Not applicable
Upper explosion limit:	Not applicable
Lower explosion limit:	Not applicable
Vapour pressure:	Not applicable
Relative vapour density:	Not applicable
Density:	Not applicable
Bulk density:	Not carried out
Solubility in water:	Not carried out
Solubility in other solvents:	Not performed
Partition coefficient: n-octanol/water:	No data available
Ignition temperature:	Not applicable
Auto-ignition temperature:	Not applicable
Thermal decomposition:	Method: No data available
Viscosity	
Viscosity, dynamic:	Not carried out
Viscosity, kinematic:	Not carried out
Explosive properties:	Not applicable
Oxidising properties:	Not applicable
<u>9.2 Other information</u>	
Surface tension:	Not performed
Sublimation point:	Not applicable

## **SECTION 10: Stability and reactivity**

### 10.1 Reactivity:

There are no particular risks of reaction with other substances under normal conditions of use.

### 10.2 Chemical Stability:

The product is stable under normal use and storage conditions.

### 10.3 Potentially hazardous reactions:

None.

### 10.4 Conditions to avoid

Stable under normal conditions.

### 10.5 Chemically Interacting Materials:

None in particular.

### 10.6 Hazardous decomposition products:

None.

## **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects:

#### **Toxicological information of the product**

N/A

#### **Toxicological information of the main substances contained in the product:**

Dipropylene glycol, dibenzoate - CAS: 27138-31-4

# Safety Data Sheet

In accordance with directive 1907/2006/EC, 2015/830

Page: Page 6 of 9

Version 1.0

Date of issue: 28-08-2020

Print date: 29-6-2021

Trade name: Polyurethane

Casting Resin Flexible A60 B

(a) acute toxicity:

Test: LD50 - Route: oral 3,914 mg / kg

Test: LD50 - Route: Skin 2,000 mg / kg

Test: LC50 - Route: Inhalation > 200 mg/l - Duration: 4 hours

Dietilmetilbenzendammina - CAS: 68479-98-1

(a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rat > 2,000 mg / kg

Test: LD50 - Route: Skin - Species: Rabbit > 2,000 mg / kg

(i) STOT on repeated exposure:

Route: Oral - Species: Rat 4 4 mg / kg

If not otherwise specified, the information required by Regulation (EU) 2015/830 below should be considered as N/A:

(a) acute toxicity;

b) skin corrosion/irritation;

c) serious eye damage/irritation;

(d) respiratory or skin sensitisation;

(e) mutagenicity in germ cells;

(f) carcinogenicity;

(g) reproductive toxicity;

(h) STOT single exposure;

(i) STOT on repeated exposure;

(j) hazard of aspiration.

## **SECTION 12: Ecological information**

### **12.1 Toxicity:**

Apply good working practices so that the product does not end up in the environment.

Dietilmetilbenzendammina - CAS: 68479-98-1

a) Acute aquatic toxicity:

Endpoint: LC50 - Species: Fish > 104 mg/l - Duration: 96

Endpoint: EC50 - Species: Daphnia = 5.8 mg/l - Duration u: 48

Endpoint: IC50 - Species: Algae = 104 mg/l - Duration: 72

Endpoint: LC50 - Species: Daphnia = 0.5 mg/l - Duration u: 48

(c) Bacterial toxicity:

Endpoint: EC50 - Species: BATTERI = 170 mg / l - Duration: 24

### **12.2 Persistence and Degradability:**

Biodegradability: No data available.

Dipropylene glycol, dibenzoate - CAS: 27138-31-4

Biodegradability: Readily biodegradable.

Dietilmetilbenzendammina - CAS: 68479-98-1

Biodegradability: Not readily biodegradable

### **12.3 Bioaccumulation:**

Bioaccumulation: Information not available

Dipropylene glycol, dibenzoate - CAS: 27138-31-4

Bioaccumulation: not bioaccumulative

Dietilmetilbenzendammina - CAS: 68479-98-1

Bioaccumulation: briefly bioaccumulative.

### **12.4 Mobility in Soil:**

Mobility in soil: No data available

Dipropylene glycol, dibenzoate - CAS: 27138-31-4

Mobility in soil: It evaporates quickly.

Dietilmetilbenzendammina - CAS: 68479-98-1

Mobility in soil: No data available

# Safety Data Sheet

In accordance with directive 1907/2006/EC, 2015/830

Page: Page 7 of 9

Version 1.0

Date of issue: 28-08-2020

Print date: 29-6-2021

Trade name: Polyurethane

Casting Resin Flexible A60 B

## 12.5 Results of PBT and vPvB assessment

vPvB-substances: None - PBT Substances None

## 12.6 Other Harmful Effects:

None.

## **SECTION 13: Instructions for disposal**

### 13.1 Waste treatment methods:

Repair if possible. Observe the applicable local and national regulations.

## **SECTION 14: Information relating to carriage**

### 14.1 UN number

ADR-UN number: 3082

IATA-UN number: 3082

IMDG-UN number: 3082

### 14.2 Proper load name according to UN Model Regulations

ADR shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Dipropylene glycol, dibenzoate)

IATA technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Dipropylene glycol, dibenzoate)

IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS LIQUID, N.O.S.  
(Dipropylene glycol, dibenzoate)

### 14.3 Transport hazard class(es)

ADR-class: 9

ADR label: 9

ADR - Hazard identification number: 90

IATA Class: 9

IATA label: 9

IMDG Class: 9

### 14.4 Packing group

ADR packing group: III

IATA Packing group: III

IMDG Packing group: III

### 14.5 Environmental hazards

Marine pollutant: No

### 14.6 Special precautions for the user

ADR Tunnel Restriction Code: E

Track (RID): 9

Railway (RID): 3082

IMDG-Technical name: ENVIRONMENTALLY HAZARDOUS LIQUID, N.O.S.  
(Dipropylene glycol, dibenzoate)

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No.

## **SECTION 15: Legally required information**

### 15.1 Safety, health and environmental regulations and legislation specific to the substance or mixture

Dir. 98/24 / EC (Risks related to chemical agents at work)

Dir. 2000/39 / EC (occupational exposure limits)

Regulation (EC) No 1907/2006 (REACH)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EC) 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) No 286/2011 (ATP 2 CLP)

# Safety Data Sheet

In accordance with directive 1907/2006/EC, 2015/830

Page: Page 8 of 9

Version 1.0

Date of issue: 28-08-2020

Print date: 29-6-2021

Trade name: Polyurethane

Casting Resin Flexible A60 B

Regulation (EU) No 618/2012 (ATP 3 CLP)

Regulation (EU) No 487/2013 (ATP 4 CLP)

Regulation (EU) No 944/2013 (ATP 5 CLP)

Regulation (EU) No 605/2014 (ATP 6 CLP)

Regulation (EU) No 2015/1221 (ATP 7 CLP)

Regulation (EU) 2016/918 (ATP 8 CLP)

Regulation (EU) 2016/1179 (ATP 9 CLP)

Regulation (EU) 2017/776 (ATP 10 CLP)

**Restrictions on the product or substances in Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent amendments:**

No

**Please refer to the following legal provisions, if applicable:**

Directive 2012/18 / EU (Seveso III)

Regulation (EC) No 648/2004 (detergents).

Dir. 2004/42 / EC (VOC Directive)

**Provisions relating to Directive EU 2012/18 (Seveso III):**

Seveso III category according to Annex 1, Part 1

**Product belongs to category: E2**

15.2 Chemical safety assessment:

No chemical safety assessment has been carried out for the mixture.

## **SECTION 16: Other information**

### **Full text of the H statements**

H412 Harmful to aquatic life with long lasting effects.

H312 Harmful in contact with skin.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H400 Very toxic to aquatic organisms.

H410 Very toxic to aquatic life with long lasting effects.

### **Full text of other abbreviations**

Acute tox. 4	3.1 / 4 /	Dermal Acute toxicity (dermal) category 4
Acute tox. 4	3.1 / 4 /	Oral Acute toxicity, category 4
Eye Irrit. 2	3.3 / 2	Eye irritation, category 2
STOT RE 2	3.9 / 2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Acute 1	4.1 / A1	Acute aquatic hazard category 1
Aquatic Chronic 1	4.1 / C1	Chronic (long-term) aquatic hazard, Category 1
Aquatic Chronic 2	4.1 / C2	Chronic (long-term) aquatic hazard, Category 2
Aquatic Chronic 3	4.1 / C3	Chronic (long-term) aquatic hazard, Category 3

This Safety Data Sheet has been fully updated in accordance with Regulation 2015/830.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

### **Classification according to Regulation (EC) No 1272/2008**

#### **Classification procedure**

Eye Irrit. 2, H319	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document has been drawn up by a competent person who has undergone appropriate training.



# Safety Data Sheet

In accordance with directive 1907/2006/EC, 2015/830

Page: Page 9 of 9

Version 1.0

Date of issue: 28-08-2020

Print date: 29-6-2021

Trade name: Polyurethane

Casting Resin Flexible A60 B

Main bibliographical sources:

ECDIN - Data and Information Network on Environmental Chemicals - Joint Research Centre, Commission of the European Communities

THE DANGEROUS PROPERTY OF SAX FROM INDUSTRIAL MATERIALS - Eighth Edition - Van Nostrand Reinold

The information contained in this document is based on our knowledge at the date specified above. It refers exclusively to the product indicated and does not constitute a guarantee for any particular quality.

It is the user's duty to ensure that this information is appropriate and complete in relation to the specific intended use.

This MSDS cancels and replaces all previous releases.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute toxicity estimation
ATEmix:	Acute toxicity estimation (mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	classification, labelling, packaging.
DNEL:	Derived dose without effect.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally harmonised system for classification and labelling of chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the International Air Transport Association (IATA).
ICAO:	International Civil Aviation Organisation.
ICAO-TI:	Technical Instructions of the International Civil Aviation Organization (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Fatal concentration, for 50 percent of the test population.
LD50:	Lethal dose, for 50 percent of the test population.
PNEC:	Predicted no-effect concentration.
RID:	Regulation on the International Carriage of Dangerous Goods by Rail.
STEL:	Short-term exposure limit.
STOT:	Specific target organ toxicity.
TLV:	Threshold Limiting Value.
TWA:	time-weighted average
WGK:	German water hazard class.