

TECHNICAL INFORMATION SHEET

SRA 6200

SRA 6200 is a multi-purpose, medium duty, silicone mould release agent. It is based on silicones and has been formulated as a highly effective, multi-purpose release agent for most waxes, plastics and rubber moulding purposes.

SRA 6200 provides a medium duty film for release of wax, plastic and rubber parts in injection moulding, compression moulding, vacuum forming and many other moulding and forming processes. It will not build up in the mould and helps to improve surface finish, reduce rejects and increases production. Fitted with 360° spray system for use at any angle, even upside down.

Shake well before use, spray a light even coating from 9" - 12" (25 - 30 cm) and re-apply as necessary.

TYPICAL PROPERTIES

Appearance Clear, colourless liquid

Odour Hydrocarbon

SG @ 25°C 0.723

Pressure @ 25°C 3.5 Bar

Discharge rate 0.8 q/sec

Solubility Soluble in solvents, insoluble in water

Flammability Classified as extremely flammable under current EC Regulations

Packaging 400 ml aerosol (12 per carton)

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 30°C, away from direct heat and naked flames.

HEALTH AND SAFETY

Health and safety data sheet available separately.

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.