

Material: 60007401 ELASTOSIL® M 4370 A

Version: 2.6 (GB) Date of print: 09.04.2020 Date of last alteration: 19.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial product name: ELASTOSIL® M 4370 A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:

Industrial.

Raw material for: elastomer products.

1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor: Wacker Chemie AG
Street/POB-No.: Hanns-Seidel-Platz 4
State/postal code/city: D 81737 München
Telephone: +49 89 6279-0
Telefax: +49 89 6279-1770

Information about the Safety Data Sheet: Telephone +49 8677 83-4888
Telefax +49 8677 886-9722

eMail WLCP-MSDS@wacker.com

1.4 Emergency telephone number

Emergency Information: +44 1273 289451

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008:

Not a hazardous substance or mixture.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008:

No labeling according to GHS required.

| Code | Additional Labelling |
|--------|---|
| EUH210 | Safety data sheet available on request. |

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

Polydimethylsiloxane with functional groups and auxiliaries for addition cross-linking

3.2.2 Hazardous ingredients

| Typ | oe (| CAS No. | EC-No. | Substance | Content % | | Comment |
|-----|------|------------|-----------|-----------|-----------|---|---------|
| | | | REACH no. | | | according to Regulation (EC) No. 1272/2008* | |
| INF | HA | 14808-60-7 | 238-878-4 | Quartz | >50 – <60 | STOT RE 1 by inhalation; H372 | [1] |

Type: INHA: ingredient, VERU: impurity

Page: 1/9



Material: 60007401 ELASTOSIL® M 4370 A

Version: 2.6 (GB) Date of print: 09.04.2020 Date of last alteration: 19.11.2019

[1] = Hazardous or environmentally harmful substance; [2] = substance with a Community workplace exposure limit; [3] = PBT substance; [4] = vPvB substance

*Classification codes are explained in section 16.

Quartz: This component does not impact the product's hazard classification. Due to the product's physical properties, particulate inhalation exposure is not possible.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above ≥ 0.1%.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).

After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

After contact with the skin:

Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

After inhalation:

Provide fresh air.

After swallowing:

Give several small portions of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

alcohol-resistant foam, carbon dioxide, water mist, sprinkler system, sand, extinguishing powder.

Extinguishing media which must not be used for safety reasons:

water jet .

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: toxic and very toxic fumes .

5.3 Advice for firefighters

Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air. Keep unprotected persons away.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.



Material: 60007401 ELASTOSIL® M 4370 A

Version: 2.6 (GB) Date of print: 09.04.2020 Date of last alteration: 19.11.2019

6.3 Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Precautions for safe handling:

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

Precautions against fire and explosion:

Observe the general rules for fire prevention.

7.2 Conditions for safe storage, including any incompatibilities

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Maximum airborne concentrations at the workplace:

not applicable

8.2 Exposure controls

8.2.1 Exposure in the work place limited and controlled

General protection and hygiene measures:

Observe standard industrial hygiene practices for the handling of chemical substances. Do not eat, drink or smoke when handling.

Personal protection equipment:

Respiratory protection

No personal respiratory protective equipment normally required.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Filtering half-face mask, according to acknowledged standards such as EN 149.

Recommended Filter type: FFP1 or equivalent filter, according to acknowledged standards such as EN 149

Observe the equipment manufacturer's information and wear time limits for respirators.

Eye protection

Recommendation: protective goggles .

Hand protection

Use of protective gloves is recommended when handling the material.

Page: 3/9



Material: 60007401 ELASTOSIL® M 4370 A

Version: 2.6 (GB) Date of print: 09.04.2020 Date of last alteration: 19.11.2019

Recommended glove types: Protective gloves made of nitrile rubber

thickness of the material: > 0,1 mm Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of butyl rubber

thickness of the material: > 0,3 mm Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

8.3 Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

SECTION 9: Physical and chemical properties

| 9.1 | Information on basic physical and chemical properties | | | |
|-----|---|---------------------------------|--------------|--|
| | Property: | Value: | Method: | |
| | Appearance | | | |
| | Physical state: | liquid | | |
| • | Colour: | | | |
| | Odour | | | |
| | Odour | odourless | | |
| • | Odour limit | | | |
| | Odour limit | no data available | | |
| | pH-Value | | | |
| | pH-Value | not applicable | | |
| | Melting point/freezing point | | | |
| | Melting point / melting range | not applicable | | |
| | Initial boiling point and boiling range | | | |
| | Boiling point / boiling range | not applicable | | |
| | Flash point | • | | |
| | Flash point | > 200 °C | (DIN 51376) | |
| | Evaporation rate | | , | |
| | Evaporation rate | no data available | | |
| | Upper/lower flammability or explosive limits | | | |
| | Lower explosion limit (LEL) | | | |
| | Upper explosion limit (UEL) | not applicable | | |
| | Vapour pressure | | | |
| | Vapour pressure: | not applicable | | |
| | Solubility(ies) | | | |
| | Water solubility / miscibility: | virtually insoluble | | |
| | Vapour density | | | |
| | Relative gas/vapour density | No data known. | | |
| | Relative Density | | | |
| | Relative Density | | (DIN 51757) | |
| | | (Water / 4 °C = 1,00) | | |
| | Density | ca. 1,5 g/cm³ (25 °C; 1013 hPa) | (DIN 51757) | |
| | Partition coefficient: n-octanol/water | | | |
| | Partition coefficient: n-octanol/water | No data known. | | |
| | Auto-ignition temperature | | | |
| | Ignition temperature | > 450 °C | (DIN 51794) | |
| | Decomposition temperature | | | |
| | Thermal decomposition: | > 200 °C | | |
| | Viscosity | 40000 05000 B 40000 | (D. 16.15) | |
| | Viscosity (dynamic): | 10000, - 25000, mPa.s at 23 °C | (Brookfield) | |



Material: 60007401 ELASTOSIL® M 4370 A

Version: 2.6 (GB) Date of print: 09.04.2020 Date of last alteration: 19.11.2019

Molecular mass

Molecular mass not applicable

9.2 Other information

No data available.

SECTION 10: Stability and reactivity

10.1 - 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

none known

10.5 Incompatible materials

none known

10.6 Hazardous decomposition products

If stored and handled properly: none known . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Product details:

| Route of expo | osure Result/Effect | Species/Test system | Source |
|---------------|---------------------|---------------------|---------------|
| Oral | LD50: > 2000 mg/kg | Rat | Conclusion by |
| | | | analogy |
| dermal | LD50: > 2000 mg/kg | Rat | Conclusion by |
| | | | analogy |

11.1.2 Skin corrosion/irritation

Product details:

| Result/Effect | Species/Test system | Source |
|----------------|---------------------|---------------|
| not irritating | Rabbit | Conclusion by |
| | | analogy |

11.1.3 Serious eye damage / eye irritation

Product details:

| Result/Effect | Species/Test system | Source |
|----------------|---------------------|---------------|
| not irritating | Rabbit | Conclusion by |
| | | analogy |

11.1.4 Respiratory or skin sensitization

Product details:

| Route of expo | osure Result/Effect | Species/Test system | Source |
|---------------|---------------------|--------------------------|---------------|
| dermal | not sensitizing | Guinea pig; Buehler Test | Conclusion by |
| | | | analogy |
| | | | OECD 406 |

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.



Material: 60007401 ELASTOSIL® M 4370 A

Version: 2.6 (GB) Date of print: 09.04.2020 Date of last alteration: 19.11.2019

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

SECTION 12: Ecological information

12.1 Toxicity

Assessment:

Assessment based on ecotoxicological tests with similar products under consideration of the physical-chemical properties: For this product no effects on aquatic organisms, relevant for classification, are expected. According to current knowledge adverse effects on water purification plants are not expected.

12.2 Persistence and degradability

Assessment:

Silicone content: biologically not degradable. Separation by sedimentation.

12.3 Bioaccumulative potential

Assessment:

Polymer component: No adverse effects expected.

12.4 Mobility in soil

Assessment:

Silicone content: Insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

none known

12.7 Additional information

Easily separable from water by filtration.

Page: 6/9



Material: 60007401 ELASTOSIL® M 4370 A

Version: 2.6 (GB) Date of print: 09.04.2020 Date of last alteration: 19.11.2019

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Material

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

13.1.3 Waste Disposal Legislation Ref.No.(EC)

It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

SECTION 14: Transport information

14.1 - 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

Road ADR:

Valuation Not regulated for transport

Railway RID:

Valuation Not regulated for transport

Transport by sea IMDG-Code:

Valuation Not regulated for transport

Air transport ICAO-TI/IATA-DGR:

Valuation Not regulated for transport

14.5 Environmental hazards

Hazardous to the environment: no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances (Seveso III):

Not applicable

Relevant regulations:

SI 2002/1689: CHIP Regulations 2002 SI 2002/2677: COSHH Regulations 2002

SI 1999/3242: Management of Health & Safety at Work Regulations 1999

Health & Safety at Work Act 1974

SI 1993/1643: Environmental Protection Act 1993 & Subsidiary Regulations.

Other national and local measures relating to the workplace, pollution control, environmental protection and waste control.



Material: 60007401 ELASTOSIL® M 4370 A

Version: 2.6 (GB) Date of print: 09.04.2020 Date of last alteration: 19.11.2019

Other specifications, restrictions and prohibitions:

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals: Not applicable

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

This product is listed in, or complies with, the substance inventory.

China.....: IECSC (Inventory of Existing Chemical Substances in China):

This product is listed in, or complies with, the substance inventory.

Canada DSL (Domestic Substance List):

This product is listed in, or complies with, the substance inventory.

United States of America (USA).....: TSCA (Toxic Substance Control Act Chemical Substance Inventory):

All components of this product are listed as active or are in compliance with the

substance inventory.

Taiwan TCSI (Taiwan Chemical Substance Inventory):

This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of

this obligation.

European Economic Area (EEA).....: REACH (Regulation (EC) No 1907/2006):

General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA

by customers or other downstream users must be fulfilled by the latter. South Korea (Republic of Korea): AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"):

General note: in case of registration obligations for substances or polymers imported into Korea or manufactured within Korea these are fulfilled by the supplier mentioned in section 1. The registration obligations for substances or polymers imported into Korea by customers or other downstream users must be fulfilled by

the latter.

SECTION 16: Other information

16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

Page: 8/9



Material: 60007401 ELASTOSIL® M 4370 A

Version: 2.6 (GB) Date of print: 09.04.2020 Date of last alteration: 19.11.2019

Explanation of the GHS classification code:

STOT RE 1; H372: Specific target organ toxicity - repeated exposure Category 1; Causes damage to organs through

prolonged or repeated exposure if inhaled.

- End of Safety Data Sheet -