



©2016 Chem-Trend L.P.

# Chemlease® Mold Cleaner EZ

## Description

Chemlease® Mold Cleaner EZ is a special blend of solvents designed to dissolve and remove wax and dirt from composite molds. Ideal for preparing composite mold surfaces for the application of Chemlease® Mold Sealers and Releases. Also excellent for cleaning brushes and equipment.

## Application

1. Chemlease® Mold Cleaner EZ should be applied to the mold surface with a clean 100% cotton cloth (we recommend our Chemlease® Cotton Cloth). While the mold surface is still wet, vigorously wipe the mold dry with a second clean, dry 100% cotton cloth.
  2. Frequently exchange saturated cloths with new, clean cloths.
  3. Repeat process several times until all residue (dirt, dust, grease, moisture, etc.) is removed (at least two cleanings are recommended.)
1. The mold is then ready for application of Chemlease® Mold Sealer and/or Chemlease® Mold Release.

## Note:

If you plan to use compounds or glazes etc. prior to applying Sealer and/or Mold Release, be sure to wipe clean with Chemlease® Mold Cleaner EZ after doing so, as most buffing compounds will not allow Chemlease® Sealers and Release Agents to work properly. Prolonged exposure on the mold surface (puddling, dipping, etc.) should be avoided.

## Storage

Recommended storage temperature is between 10°C and 35°C. Keep container tightly sealed to prevent evaporation and/or contamination. If stored in cold temperatures, allow product to warm to room temperature prior to use.

## Handling

For more information on storage, handling, hazards, etc., please request a copy of Chem-Trend's Material Safety Data Sheet, which must be consulted prior to use of this product.

## Packaging

Product is available in a variety of packaging. Please contact our customer service team for details.

## Further Information

Request information on our complete range of materials for this industry.

## Legal Notice

The technical information and suggestions for use contained herein is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a professional with technical experience. It does not release the customer from the obligation of performing own tests with the product selected for a specific application. While the information and suggestions are believed to be accurate and reliable, nothing stated in this bulletin is to be taken as a warranty either expressed or implied.