

# Deep Epoxy Resin A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Date of issue: 07/01/2013

Revision date: 05/08/2015

Supersedes: 01/12/2014

Version: 1.4

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Deep Epoxy Resin A  
Type of product : Resin

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use  
Industrial/Professional use spec : Intended for general public  
Industrial  
Use of the substance/mixture : Industrial laminating resin, casting, injection, winding, infusion, gluing, foaming, coatings and sealants

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Nedform BV  
Hofdarsweg 20, 6161DD Geleen, The Netherlands  
Tel: +31(0)464106260 Mail: [info@resoltech.com](mailto:info@resoltech.com)  
[www.nedform.com](http://www.nedform.com)

#### 1.4. Emergency telephone number

Emergency number : ORFILA (FRANCE) : +33 (0)1 45 42 59 59 (24h/24, 7j/7)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	NPIS Edinburgh (Scottish Poisons Information Bureau) Royal Infirmary of Edinburgh, Centre Hospitalier Universitaire Bab el Oued	51 Little France Crescent EH16 4SA Edinburgh	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Centre Hospitalier Universitaire de Constantine	Avonley Road SE14 5ER London	0870 243 2241	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2 H319  
Sensitisation — Skin, Category 1 H317  
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS09

Signal word (CLP) : Warning

# Deep Epoxy Resin A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Hazardous ingredients	: C13/C15-Alkylglycidylether; reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq$ 700); Formaldehyde, polymer with (chloromethyl)oxirane and phenol
Hazard statements (CLP)	: H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (CLP)	: P102 - Keep out of reach of children P270 - Do not eat, drink or smoke when using this product P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician P281 - Use personal protective equipment as required P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation
EUH-statements	: EUH205 - Contains epoxy constituents. May produce an allergic reaction

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq$ 700)	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8 (REACH-no) 01-2119456619-26	50 - 70	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
C13/C15-Alkylglycidylether	(CAS No) 68081-84-5 (EC no) 268-358-2 (REACH-no) 01-2119962192-39	10 - 40	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Aquatic Chronic 3, H412
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	(CAS No) 9003-36-5 (EC no) 500-006-8 (REACH-no) 01-2119454392-40	10 - 40	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Eye Irrit. 2, H319

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq$ 700)	(CAS No) 25068-38-6 (EC no) 500-033-5 (EC index no) 603-074-00-8 (REACH-no) 01-2119456619-26	(C $\geq$ 5) Skin Irrit. 2, H315 (C $\geq$ 5) Eye Irrit. 2, H319

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Allow the victim to rest. Allow breathing of fresh air. Give oxygen or artificial respiration if necessary. If breathing stops, give artificial respiration. Call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Take off contaminated clothes, wash skin with plenty of water or have a shower (during minimum 15 minutes) and if necessary take medical advice. Be careful, the product may remain trapped under clothing, footwear or a wrist-watch. Do not use solvents or thinners. If on skin and if skin irritation or rash occurs, seek medical advice and attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist immediately.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

# Deep Epoxy Resin A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.
- Symptoms/injuries after skin contact : Causes skin irritation. May cause moderate irritation,. This material or its emissions may induce an allergic or sensitization reaction and thereby aggravate existing systemic disease.
- Symptoms/injuries after eye contact : Causes eye irritation. May cause moderate irritation, including burning sensation, tearing, redness or swelling.

### 4.3. Indication of any immediate medical attention and special treatment needed

For the Anti-poison Center indicate all the components including the non dangerous ones to obtain (when possible) a total of 100 %.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Water spray. Dry powder. Alcohol resistant foam.
- Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

- Explosion hazard : Heat may cause pressure rise with explosion of tanks/drums.
- Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide. Nitrogen oxides. Toxic fumes.

### 5.3. Advice for firefighters

- Firefighting instructions : Evacuate the danger area. Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : Exercise caution when fighting any chemical fire.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Protective equipment : Manipulations are to be done only by qualified and authorised persons. Wear recommended personal protective equipment.
- Emergency procedures : If a major spill occurs, all personnel should be immediately evacuated and the area ventilated.

#### 6.1.2. For emergency responders

- Protective equipment : Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. Wear proper protective equipment.
- Emergency procedures : Stop release. Place in an appropriate container and dispose of the contaminated material at a licensed site.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.

### 6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store, if possible, in a cool, well ventilated place away from incompatible materials. Keep container closed when not in use.
- Incompatible products : Oxidizing agent. Strong bases. Strong acids.
- Storage area : Store in a well-ventilated place.
- Special rules on packaging : Store in a closed container.

### 7.3. Specific end use(s)

No additional information available

# Deep Epoxy Resin A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

#### 8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure. Gas mask. Protective clothing. In case of splash hazard: safety glasses. Gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hand protection	: Nitrile-rubber protective gloves. Chemical resistant gloves (according to European standard NF EN 374 or equivalent)
Eye protection	: Chemical goggles or face shield
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear respiratory protection. Gas mask with filter type A



Consumer exposure controls	: Avoid contact during pregnancy/while nursing.
Other information	: Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid.
Colour	: Colourless.
Odour	: slight.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.08
Relative density of saturated gas/air mixture	: 1.08
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

# Deep Epoxy Resin A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

### 10.2. Chemical stability

Stable under use and storage conditions as recommended in section 7.

### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

### 10.4. Conditions to avoid

No data available.

### 10.5. Incompatible materials

Strong acids. Oxidizing agent. Strong bases. Amines.

### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. Nitrogen oxides. Toxic fumes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

ATE CLP (oral)	500.000 mg/kg bodyweight
ATE CLP (dermal)	1100.000 mg/kg bodyweight

<b>C13/C15-Alkylglycidylether (68081-84-5)</b>	
LD50 oral rat	> 5000 mg/kg

<b>reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</b>	
LD50 oral rat	11400 mg/kg
LD50 oral	≈ 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

<b>Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)</b>	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: No data.
Ecology - air	: No data.
Ecology - water	: No data.

<b>reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)</b>	
LC50 fish 1	1.3 mg/l
EC50 Daphnia 1	2.1 mg/l
EC50 72h algae (1)	11 mg/l

<b>Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)</b>	
LC50 fish 1	2.54 mg/l
EC50 Daphnia 1	2.55 mg/l
EC50 72h algae (1)	> 1000 mg/l

### 12.2. Persistence and degradability

<b>Deep Epoxy Resin A</b>	
Persistence and degradability	No data.

# Deep Epoxy Resin A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

### 12.3. Bioaccumulative potential

#### Deep Epoxy Resin A

Bioaccumulative potential	No data.
---------------------------	----------

### 12.4. Mobility in soil

#### Deep Epoxy Resin A

Ecology - soil	No data.
----------------	----------

### 12.5. Results of PBT and vPvB assessment

#### Component

Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
---	---

### 12.6. Other adverse effects

Other adverse effects : No data.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Do not flush down sewers. Dispose of this material and its container at hazardous or special waste collection point.

Waste disposal recommendations : Recycle or dispose of in compliance with current legislation.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR) : 3082

UN-No. (IMDG) : 3082

UN-No. (IATA) : 3082

UN-No. (ADN) : 3082

UN-No. (RID) : 3082

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.

Proper Shipping Name (ADN) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Proper Shipping Name (RID) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Transport document description (ADR) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, (E)

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III, ENVIRONMENTALLY HAZARDOUS

Transport document description (ADN) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, ENVIRONMENTALLY HAZARDOUS


Transport document description (RID) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III, ENVIRONMENTALLY HAZARDOUS

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 9

Danger labels (ADR) : 9



#### IMDG

Transport hazard class(es) (IMDG) : 9

Danger labels (IMDG) : 9

# Deep Epoxy Resin A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010



### IATA

Transport hazard class(es) (IATA) : 9


Hazard labels (IATA) : 9



### ADN

Transport hazard class(es) (ADN) : 9


Danger labels (ADN) : 9



### RID

Transport hazard class(es) (RID) : 9

Danger labels (RID) : 9



#### 14.4. Packing group

Packing group (ADR) : III

Packing group (IMDG) : III

Packing group (IATA) : III

Packing group (ADN) : III

Packing group (RID) : III

#### 14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

#### 14.6. Special precautions for user

##### - Overland transport

Classification code (ADR) : M6

Special provisions (ADR) : 274, 335, 601, 375

Limited quantities (ADR) : 5I

Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions (ADR) : TP1, TP29

Tank code (ADR) : LGBV

# Deep Epoxy Resin A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Vehicle for tank carriage : AT  
Transport category (ADR) : 3  
Special provisions for carriage - Packages (ADR) : V12  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13  
Hazard identification number (Kemler No.) : 90  
Orange plates :



Tunnel restriction code (ADR) : E  
EAC code : •3Z

### - Transport by sea

Special provisions (IMDG) : 274, 335, 969  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP2, TP29  
EmS-No. (Fire) : F-A  
EmS-No. (Spillage) : S-F  
Stowage category (IMDG) : A

### - Air transport

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y964  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 964  
PCA max net quantity (IATA) : 450L  
CAO packing instructions (IATA) : 964  
CAO max net quantity (IATA) : 450L  
Special provisions (IATA) : A97, A158, A197  
ERG code (IATA) : 9L

### - Inland waterway transport

Classification code (ADN) : M6  
Special provisions (ADN) : 274, 335, 375, 601  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E1  
Carriage permitted (ADN) : T  
Equipment required (ADN) : PP  
Number of blue cones/lights (ADN) : 0

### - Rail transport

Classification code (RID) : M6  
Special provisions (RID) : 274, 335, 375, 601  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E1  
Packing instructions (RID) : P001, IBC03, LP01, R001  
Special packing provisions (RID) : PP1  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1, TP29  
Tank codes for RID tanks (RID) : LGBV  
Transport category (RID) : 3



# Deep Epoxy Resin A

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Special provisions for carriage – Packages (RID) : W12  
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31  
Colis express (express parcels) (RID) : CE8  
Hazard identification number (RID) : 90

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IBC code : Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

Not applicable

## SECTION 16: Other information

Indication of changes:

Revision - See : \*.

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : Information in this safety data sheet is based on actual knowledge in our possession and our experience. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. It is the user's responsibility to take the mentioned precautionary measures and to ensure that this information is complete and sufficient for the use of this product.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
EUH205	Contains epoxy constituents. May produce an allergic reaction

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*