

Safety Data Sheet

Material: 60053631

ELASTOSIL® M 4630 B

Version: 1.1 (INTL-GHS)

Date of print: 17.04.2019

Date of last alteration: 13.06.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial product name: ELASTOSIL® M 4630 B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:

Industrial.

Raw material for: elastomer products .

1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor:

Wacker Chemie AG

Street/POB-No.:

Hanns-Seidel-Platz 4

State/postal code/city:

D 81737 München

Telephone:

+49 89 6279-0

Telefax:

+49 89 6279-1770

Information about the Safety Data Sheet:

Telephone

+49 8677 83-4888

Telefax

+49 8677 886-9722

eMail

WLCP-MSDS@wacker.com

1.4 Emergency telephone number

Emergency Information (German):**Plant fire brigade****+49 8677 83-2222****Emergency Information (internat.):****National Response Center****+49 621 60-43333**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

2.2 Label elements

No labeling according to GHS required.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

Polydimethylsiloxane with functional groups and auxiliaries for addition cross-linking

3.2.2 Hazardous ingredients

This material does not contain any ingredients above the permitted limit(s).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).

After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

After contact with the skin:

Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

Safety Data Sheet

Material: 60053631

ELASTOSIL® M 4630 B

Version: 1.1 (INTL-GHS)

Date of print: 17.04.2019

Date of last alteration: 13.06.2018

After inhalation:

Provide fresh air.

After swallowing:

Give several small portions of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media:**

water mist , extinguishing powder , alcohol-resistant foam , carbon dioxide , sand .

Extinguishing media which must not be used for safety reasons:

water jet .

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: toxic and very toxic fumes .

5.3 Advice for firefighters**Special protective equipment for fire fighting:**

Use respiratory protection independent of recirculated air. Keep unprotected persons away.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

6.3 Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Precautions for safe handling:**

Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

Safety Data Sheet

Material: 60053631

ELASTOSIL® M 4630 B

Version: 1.1 (INTL-GHS)

Date of print: 17.04.2019

Date of last alteration: 13.06.2018

Precautions against fire and explosion:

Observe the general rules for fire prevention.

7.2 Conditions for safe storage, including any incompatibilities**Conditions for storage rooms and vessels:**

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Maximum airborne concentrations at the workplace:**

not applicable

8.2 Exposure controls**8.2.1 Exposure in the work place limited and controlled****General protection and hygiene measures:**

Observe standard industrial hygiene practices for the handling of chemical substances. Do not eat, drink or smoke when handling.

Personal protection equipment:**Respiratory protection**

No personal respiratory protective equipment normally required.

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Filtering half-face mask, according to acknowledged standards such as EN 149.

Recommended Filter type: FFP1 or equivalent filter, according to acknowledged standards such as EN 149

Observe the equipment manufacturer's information and wear time limits for respirators.

Eye protection

Recommendation: protective goggles .

Hand protection

Use of protective gloves is recommended when handling the material.

Recommended glove types: Protective gloves made of nitrile rubber

thickness of the material: > 0,1 mm

Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of butyl rubber

thickness of the material: > 0,3 mm

Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

8.3 Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

Safety Data Sheet

Material: 60053631

ELASTOSIL® M 4630 B

Version: 1.1 (INTL-GHS)

Date of print: 17.04.2019

Date of last alteration: 13.06.2018

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Property:	Value:	Method:
Appearance		
Physical state / form	liquid	
Colour	white	
Odour		
Odour	odourless	
Odour limit		
Odour limit :	no data available	
pH-Value		
pH-Value	not applicable	
Melting point/freezing point		
Melting point / melting range	not determined	
Initial boiling point and boiling range		
Boiling point / boiling range	not applicable	
Flash point		
Flash point	> 300 °C	(ISO 2592)
Evaporation rate		
Evaporation rate	no data available	
Upper/lower flammability or explosive limits		
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL)	not applicable	
Vapour pressure		
Vapour pressure	not determined	
Solubility(ies)		
Water solubility / miscibility	virtually insoluble at 20 °C	
Vapour density		
Relative gas/vapour density	No data known.	
Relative Density		
Relative Density	1,01 (20 °C; 1013 hPa)	(DIN 51757)
	(Water / 4 °C = 1,00)	
Density	1,01 g/cm ³ (20 °C; 1013 hPa)	(DIN 51757)
Partition coefficient: n-octanol/water		
Partition coefficient: n-octanol/water	No data known.	
Auto-ignition temperature		
Ignition temperature	> 450 °C	(DIN 51794)
Decomposition temperature		
Thermal decomposition	> 200 °C	
Viscosity		
Viscosity (dynamic)	approx. 800 mPa.s at 20 °C	(Brookfield)
Molecular mass		
Molecular mass	not applicable	

9.2 Other information

No data available.

SECTION 10: Stability and reactivity**10.1 – 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions**

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

none known

10.5 Incompatible materials

none known

Safety Data Sheet

Material: 60053631

ELASTOSIL® M 4630 B

Version: 1.1 (INTL-GHS)

Date of print: 17.04.2019

Date of last alteration: 13.06.2018

10.6 Hazardous decomposition products

If stored and handled properly: none known . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****11.1.1 Acute toxicity****Product details:**

Route of exposure	Result/Effect	Species/Test system	Source
oral	LD ₅₀ : > 2000 mg/kg	rat	Conclusion by analogy
dermal	LD ₅₀ : > 2000 mg/kg	rat	Conclusion by analogy

11.1.2 Skin corrosion/irritation**Product details:**

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy

11.1.3 Serious eye damage / eye irritation**Product details:**

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy

11.1.4 Respiratory or skin sensitization**Product details:**

Route of exposure	Result/Effect	Species/Test system	Source
dermal	not sensitizing	guinea-pig; Bühler	Conclusion by analogy OECD 406

11.1.5 Germ cell mutagenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

Safety Data Sheet

Material: 60053631

ELASTOSIL® M 4630 B

Version: 1.1 (INTL-GHS)

Date of print: 17.04.2019

Date of last alteration: 13.06.2018

11.1.10 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.

SECTION 12: Ecological information

12.1 Toxicity

Assessment:

Based on available data no effects on aquatic organisms that are relevant for classification must be expected for the product up to its limits of water solubility. According to current knowledge adverse effects on water purification plants are not expected.

12.2 Persistence and degradability

Assessment:

Silicone content: biologically not degradable. Separation by sedimentation.

12.3 Bioaccumulative potential

Assessment:

Polymer component: No adverse effects expected.

12.4 Mobility in soil

Assessment:

Silicone content: Insoluble in water.

12.5 Other adverse effects

none known

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Material

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

SECTION 14: Transport information

14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

Road ADR:

Valuation: Not regulated for transport

Railway RID:

Valuation: Not regulated for transport

Transport by sea IMDG-Code:

Valuation: Not regulated for transport

Air transport ICAO-TI/IATA-DGR:

Valuation: Not regulated for transport

14.5 Environmental hazards

Hazardous to the environment: no

Safety Data Sheet

Material: 60053631

ELASTOSIL® M 4630 B

Version: 1.1 (INTL-GHS)

Date of print: 17.04.2019

Date of last alteration: 13.06.2018

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

15.2 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

South Korea (Republic of Korea)	ECL (Existing Chemicals List): This product is listed in, or complies with, the substance inventory.
Japan	ENCS (Handbook of Existing and New Chemical Substances): This product is listed in, or complies with, the substance inventory.
Australia	AICS (Australian Inventory of Chemical Substances): This product is listed in, or complies with, the substance inventory.
People's Republic of China	IECSC (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory.
Canada	DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines.....	PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA).....	TSCA (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Taiwan (Republic of China).....	TCSI (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA).....	REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.

SECTION 16: Other information

16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

All deliveries are subject to the WACKER SILICONES Health Care Policy, which is available at www.wacker.com.

Safety Data Sheet

Material: 60053631**ELASTOSIL® M 4630 B**

Version: 1.1 (INTL-GHS)

Date of print: 17.04.2019

Date of last alteration: 13.06.2018

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

- End of Safety Data Sheet -